



Quality management
certified according to
DIN EN ISO 9001

Energy management
certified according to
DIN EN ISO 50001

Environmental management
certified according to
DIN EN ISO 14001



Product
overview



ALLROUND SHORING TG 60

LAYHER ALLROUND SCAFFOLDING




Allround equipment features a simple, unique and bolt-free connection technology. When the wedge head is pushed over the rosette, the wedge drops automatically into the recess thanks to the innovative AutoLock function and is immediately secured against being moved or falling out.



A hammer blow on the wedge transforms the positive connection into a non-positive one. The end face of the wedge head is now positioned precisely at the standard.



Up to eight connections can be made in the structurally ideal Allround connector, on one level and at various angles. Attachment is possible at the standard dimension intervals of 50 cm on all Allround standards. The flat rosette prevents clogging by dirt of any type.



Ideal transmission of high forces coupled with low weight. The wedge head and standard are harmonised in such a way that the ledger loads to be absorbed are transmitted directly to the centre of the standard. The following approvals are available for Layher Allround Scaffolding: Z-8.22-64, Z-8.22-64.1, Z-8.22-939, Z-8.22-949, Z-8.1-919 as well as other international approvals.

Ingenious technology for efficient working.

The four small punched-out openings in the rosette automatically centre the ledger at right angles – the four large openings permit alignment with free selection of the angle.

The sturdy and inexpensive Allround equipment made from (hot-dip galvanised) steel is primarily used in the field of demanding construction scaffolding.

Allround Shoring TG 60 – the benefits for you:

- Time saved when assembling and dismantling thanks to bolt-free connection technology.
- No parts can be lost.
- Small amount of material used.
- Maintenance-free, long-lasting hot-dip-galvanised components that are always ready for use.
- Low weight of individual components.
- Sophisticated range of parts.
- Excels due to cost-effectiveness and versatility.

THE COMPONENTS.



Shoring Frames TG 60 – even more possibilities for Allround Scaffolding.

The Shoring Frames TG 60 were developed on the basis of Allround Scaffolding. With just three additional parts, they can be used to create higher and more stable shoring structures even more quickly. The Shoring Frames TG 60 are available in the sizes 1.00 x 1.09 m, 0.50 x 1.09 m and 0.71 x 1.09 m.



Shoring Frame TG 60

$H = 0.50\text{ m}$

as end frame or equalising frame



The initial frame $H = 0.71\text{ m}$ is equipped with rosettes at the top and bottom and does not have any spigots. The Shoring Frames TG 60 with $H = 1.00\text{ m}$ and $H = 0.50\text{ m}$ are only equipped with Allround rosettes at the top ends of the standards. They are connected using the integrated spigots at the bottom.




Shoring Frame TG 60

$H = 1.00\text{ m}$

as frame in central tower area

Allround Shoring Frames TG 60 are manufactured from high-tensile steel scaffolding tube and stiffened using two struts. Each standard can be loaded with up to six tonnes. The welded-in ledgers are crimped at the ends to provide seven connecting points at the Allround rosette. The Shoring Frames TG 60 replace the standards, ledgers and diagonal braces, meaning that assembly and dismantling can be performed 30% faster and with fewer components.

The individual shoring frames are secured using hinged pins at the joint for transmission of any tensile forces that occur. It is therefore possible to assemble a structure horizontally at ground level before moving it into position by crane. The Shoring Frames TG 60 have a symmetrical design, with the result that no diagonal guidance has to be taken into account during assembly.



Shoring Frame TG 60

$H = 0.71\text{ m}$

as initial frame

Allround Shoring TG 60 – the benefits for you:

- Lightweight components with high load-bearing capacity.
- Faster and safer assembly and dismantling.
- Variably adaptable to loads and building geometries.
- Type tests for the individual towers of types A to E.





Costing, work preparation, planning and project handling

- Approval Z-8.22-64 regulates the manufacture and marking of Shoring Frames TG 60.
- Instructions for assembly and use and DIBt-approved load-bearing capacity tables for the individual towers based on DIN EN 12812. The TP-11-017 type test contains calculations for tower variants with different ground plans and support heights.
- Material requirements tables and costing aids incl. cost / effort values for estimating assembly times and costs.
- Excel tools for determining the ideal basic dimensions and cost calculations.
- Comprehensive seminar programme in theory and practice.
- Support with planning from Layher application engineers.

SAFER.

Flexible adjustment to geometry and load requirements




- Different Allround ledgers and diagonal braces can be used to flexibly adapt the shoring tower to geometrical and load requirements.
- TP-11-017 type test covers various individual towers with different assembly heights.

Safer assembly – with system-integrated advancing side protection



Safer upright assembly thanks to integrated and advancing side protection

- Allround Shoring TG 60 not only offers exceptional load-bearing capacity but is also safer during assembly and dismantling. If the towers are assembled upright, O-steel decks are placed in position. The frames, ledgers and diagonal braces of the next tower section are then fitted.
- The scaffolding decks are then simply positioned 1m higher, and it is possible to ascend to the secured next level directly via the Allround Shoring Frame TG 60.



Learn more on YouTube

Layher Allround Shoring TG 60
yt-tg60-en.layher.com

FLEXIBLE.

Flexibly adaptable



Increasing load-bearing capacity by grouping the shoring frames together.




Ground surfaces sloping by up to 16% can be compensated for using the equalising plate.



Compensation for height differences in the base area, e.g. for stair flights, through the use of different shoring frames and the extensive Allround Scaffolding construction kit.



Height compensation in the top area using various shoring frames.



Height compensation in the top area using an intermediate spindle for additional spindle travel.



Shoring Towers TG 60 are connected together and braced using Allround ledgers and diagonal braces in the Layher system dimensions to create birdcage scaffolding. This results in extremely strong scaffolding structures – even for very large support heights.

Safer assembly using a crane



- By pinning the joints in place, it is possible to pre-assemble entire towers horizontally on the ground and then place them by crane.
- Thanks to the highly accurate fit, tower sections can also be transported by crane and simply mounted in place.

STRONG.

Extension using the Allround Scaffolding construction kit

Because the towers are arranged in the Layher system dimensions, standard components from the Allround construction kit can be added to the scaffolding to extend it as required. This all brings about efficient, convenient and safer solutions for everyday building site work.



Integration of stairs.



Attachment of bracket deck surfaces at edge.



Side protection at the edge of a slab.



Integration of working levels.



Bridging structure / passageway in shoring scaffolding using standard Allround Scaffolding material.



Bridging structure / passageway in shoring scaffolding using the Allround FW System.

Allround Shoring TG 60 with aluminium TwixBeam as system main beam



- When the TwixBeam is combined with Shoring TG 60, significant optimisations of the load absorption, material consumption and assembly effort of the structures are possible. This is because the standard load is frequently limited by the H-20 main beam, meaning that the entire load-bearing capacity of Shoring TG 60 cannot be used to the full. The considerably higher load-bearing capacity of the TwixBeam means that heavier loads can be transmitted into the scaffolding, and the high load-bearing capacity of TG 60 is optimally used.
- Main beams can also be constructed as genuine continuous beams with the aid of the 140 mm-high insertion beam in the intermediate area of the aluminium TwixBeam, or by using the beam connector.
- Because the beam lengths are predetermined by the system, there is no need for detailed planning of the main beams with positioning and joint design. No cost-intensive sawing work is needed at the edge areas of the wooden beams.




Learn more on YouTube



Layher aluminium TwixBeam
yt-twixbeam-bau-en.layher.com

ECONOMICAL.



You can find further information on Layher SIM in the brochure [System solutions for digitalisation and software](#).

From digital planning to a successful project

Using the possibilities of digitalisation and creating added value for scaffolding construction – that is the goal of Layher SIM. Reliable 3D planning of scaffolding structures without collisions is just one of the many benefits that go far beyond pure scaffolding planning.


- Planning and scheduling certainty at every site.
- Transparency in all work steps plus cost control.
- Increase in safety and profitability for every project.
- End-to-end digital process from the 3D laser scan as a measurement to the scaffolding system with Layher SIM2Field.
- Your access to BIM.



[Learn more on YouTube](#)

Layher SIM in the construction industry
yt-sim-en.layher.com

Logistic solutions



- A special system pallet is available for the space-saving storage of Allround Shoring Frames TG 60. Thanks to the pallet's three nested levels, it can be filled with 22 frames in a single stacking level. Depending on frame type, up to four levels can be stacked above one another on a pallet. The maximum filling quantity is therefore 88 frames.
- Integrated crane eyelets permit crane transport directly to the place of use.
- A maximum of two filled pallets can be stacked on top of one another.



Extensive rental stock



- To permit cost-effective planning and cover short-term peak material requirements, our rental and returned materials centre possesses an extensive stock of Allround Shoring TG 60 that is available for rental.
- Just contact us. We will be happy to send you a quotation.

Customer proximity is a key success factor for Layher – also in a geographical sense. That is why we are present with ideas and solutions wherever our customers need us.

